

CHORUS 714 V

Product specification sheet



5 1/2" (130mm) Polyglass mid-bass.
High dynamic medium, more bass.

5 1/2" (130mm) Polyglass woofer.
High power handling.

Aerodynamic port.
Low distortion

Aluminum/Magnesium inverted dome TNV tweeter.
Extended response to 28kHz, ready for SACD.

Solid MDF construction up to 1" (25mm) width.
Non parallel inner wall structure.

OPC crossover.
Perfect staging.
New insulated Focal terminals.



- ◆ Speakers designed and manufactured by Focal.
- ◆ A sound quality never before seen at this price level.
- ◆ Amati finish.

Type	2 1/2-way bass reflex floor standing loudspeaker
Drivers	5 1/2" (130mm) Polyglass woofer 5 1/2" (130mm) Polyglass mid-bass 1" (25mm) TNV inverted dome tweeter
Frequency response (+/- 3dB)	52Hz - 28kHz
Low frequency point (- 6dB)	43Hz
Sensitivity (2.83V/1m)	91dB
Nom. impedance	8 ohms
Minimum impedance (@25°C)	4.2 ohms @ 160Hz
Max. power handling	130W
Power RMS	90W
Crossover frequency	300Hz / 3000Hz
Dimensions (HxWxD)	35 7/16" x 8 x 11 5/8" {900 x 201 x 295mm}
Net weight	35.6lbs (16kg)

*The smallest of the Chorus V floorstanders exhibits a fine form with a minimal footprint. Elaborate yet balanced, the **Chorus 714 V** benefits from two 14 cm woofers in a 2-and-a-half way configuration to deliver solid bass. Ideal for rooms of 15 to 25 m².*

