

CHORUS 705 V

Product specification sheet

Compact loudspeaker,
wall mounting supplied.
On wall solution

5" (140mm) Polyglass mid-bass.
Dynamic medium, fast and tight bass.

Aerodynamic port.
Low distortion



Aluminum/Magnesium inverted
dome TNV tweeter.
Extended response to 28kHz,
ready for SACD.

Solid MDF construction
up to 1" (25mm) width.
Non parallel inner wall structure.

OPC crossover.
Perfect staging.
New insulated Focal terminals.



- ◆ Speakers designed and manufactured by Focal.
- ◆ A sound quality never before seen at this price level.
- ◆ Amati finish.



Optional 24" (60cm) S 700 V stand.

Type	2-way bass reflex bookshelf loudspeaker
Drivers	5" (140mm) Polyglass mid-bass 1" (25mm) TNV inverted dome tweeter
Frequency response (+/- 3dB)	65Hz - 28kHz
Low frequency point (-6dB)	57Hz
Sensitivity (2.83V/1m)	89dB
Nom. impedance	8 ohms
Minimum impedance (@25°C)	3 ohms @ 200Hz
Max. power handling	100W
Power RMS	65W
Crossover frequency	3000Hz
Dimensions (HxWxD)	12 ^{3/8} x 7 ^{9/16} x 9 ^{3/4} " (315 x 192 x 248mm)
Net weight	12.5lbs (5.7kg)

Chorus 705 V is the ideal loudspeaker for installation in rooms of modest dimensions (approximately 15 m²). With a responsive and lively bass, it represents the foundations of a great system, especially when paired with the SW 700 V subwoofer.

